



Edytor  
Telefon  
faks  
e-Mail

## Scena zewnętrzna 1 / Oprawy (lista współrzędnych)

### PHILIPS MVP507 1xHPI-T1000W/220V WB/60

72250 lm, 1041.0 W, 1 x 1 x HPI-T1000W/220V/643 (Czynnik korekcyjny 1.000).



Nr.	Pozycja [m]			Rotacja [°]		
	X	Y	Z	X	Y	Z
1	-12.500	-17.500	12.500	13.0	0.0	-30.0
2	25.250	-18.000	12.500	13.0	0.0	-45.0
3	62.500	-17.500	12.500	13.0	0.0	30.0
4	62.000	52.000	12.500	13.0	0.0	150.0
5	25.250	52.000	12.500	13.0	0.0	-135.0
6	-12.000	52.000	12.500	13.0	0.0	-150.0
7	24.750	-18.000	12.500	13.0	0.0	45.0
8	24.750	52.000	12.500	13.0	0.0	135.0
9	-12.000	-18.000	12.500	13.0	0.0	-30.0
10	-12.500	51.500	12.500	13.0	0.0	-150.0
11	62.000	-18.000	12.500	13.0	0.0	30.0
12	62.500	51.500	12.500	13.0	0.0	150.0